



Arctic Wave P50

Prediluted, 50/50, Heavy-Duty, Precharged Antifreeze/Coolant

Industry Standards

Arctic Wave P50 meets the following industry specifications:

- ASTM D3306
(automotive/light-duty)
- ASTM D4985
(heavy-duty diesel/low silicate)
- ASTM D6210/11
(fully formulated and precharged)
- TMC of ATA RP 329/330*
- TMC of ATA RP302A

**The Maintenance Council of the American Trucking Assoc. Antifreeze also meets the non-phosphate requirements of European OEM's and non-silicate requirements of Japanese OEM's*



Arctic Wave P50 appearance

Arctic Wave P50, our Prediluted Heavy-Duty antifreeze/coolant is ready to add to your vehicle cooling system; no further dilution is necessary. It is a non-silicate, non-phosphate formulation that contains the initial charge of supplemental coolant additive (SCA) and a minimum of 1200 ppm Nitrite (as NO₂). It provides outstanding protection from cavitation erosion/corrosion in water pumps and wet sleeve cylinder liners, as well as excellent overall corrosion protection. **Arctic Wave P50** is dyed to a purple color.

In addition, **Arctic Wave P50** contains an advanced inhibitor system that provides a wide range of inhibitors which protect all cooling system metals. Together with the glycol base, these inhibitors combined with other additives, give year-round protection against freeze-ups, boil-overs and engine cooling system corrosion. **Arctic Wave P50** also includes ingredients to disperse minor oil leakage, prevent fouling, control hot surface scaling and it will not damage auto finishes or rubber parts.

In automobiles, light trucks, SUV's, vans and other light duty applications, this product will provide a service life in excess of 5 years or 150,000 miles. In heavy-duty diesel applications (in which a formal monitoring and maintenance program is in place) it can provide a service life of 300,000 miles with the addition of our heavy-duty supplemental coolant additive as needed.

Arctic Wave P50 is available in 55 gallon drums and 275 gallon totes.

PHYSICAL PROPERTIES

Antifreeze Glycols	mass %	48.0 min.
Corrosion Inhibitors	mass %	1.1 min.
Water	mass %	49.0 max.
Flash Point	°F	None
Weight per gallon at 60° F-16° C	lbs.	8.9 min.
Silicates	mass %	< 250 ppm

% Antifreeze	50%	
Freezing Point	°F	-34 max
	°C	-36 max
Boiling Point*	°F	226 min
	°C	107 min

**Boiling point shown at atmospheric pressure.
Add 40°F for 15 psi radiator cap.*

Arctic Wave P50

Characteristic	Specification	Typical	ASTM Method
Chloride	25 ppm, max.	3	D3634
Specific gravity, 60/60°F	1.065 min	1.075	D1122
Nitrite	1200 ppm min	1400	D5827
Boiling Point, 50% V/V	226°F/107°C min.	229	D1120
Freezing Point, 50% V/V	-34°F/-36°C min.	-34	D1177
Effect on engine or vehicle finish	No effect	Pass	--
Ash content, mass %	2.5 max.	2.0	D1119
pH, 50% V/V	9.5-10.8	10.5	D1287
Reserve alkalinity	None specified	5 min.	D1121
Water mass %	None specified	49.0 max.	D1123
Color	Distinctive	Purple	--
Effect on nonmetals	No adverse effect	Pass	--
Storage stability	None specified	> 1 year	--
Foaming	150 ml vol., max. 5 sec. break, max.	Pass	D1881

NOTE: Used antifreeze coolant in most states is not hazardous unless it contains more than 5 ppm of lead. We recommend that spent coolant never be disposed of by dumping into a storm sewer or onto the ground. Instead, contact your local municipality for instructions on where to and how to properly dispose of this coolant and protect our environment.