

SHEARGLIDE® VO 659

Drawing Oil

Description

Shearglide® VO 659 is a heavy-duty vanishing lubricant intended for use in bending, laminating, and stamping operations on ferrous and non-ferrous metals. Any residue that might remain is easily removed with solvent or an alkaline cleaner. If cleaning is not performed, the film left behind will evaporate if parts have time to sit before shipping. Dry time is generally 60 minutes or less depending on conditions.

Shearglide® VO 659 is blended from highly refined quality base oil, so it is virtually odorless. Its low viscosity ensures little carry-off to provide reduced consumption and economy of operation.

Shearglide® VO 659 is used as received and without dilution. It can be applied using drip, drip, spray, brush, or roller methods.

Shearglide® VO 659 will evaporate if parts have time to sit before shipping. This reduces or removes the need to clean parts.

Features/Benefits

Used Neat, Requiring no Dilution

No Post Operation Cleaning Required

Contains a Lubricity Agent
Higher content than a typically vanishing type product.

May be Applied by:

Dipped, Dripped, Spray, Brushed or Rolled

Physical and Chemical Properties

Property	Value
Density, lb/gal	6.9
Color	Amber
Odor	Very Low
Flash Point, °F	142
Sulfur	None
Chlorine	None
Lubricity Agen	Present