


Product	<b>SINOPEC TULUX CF-2 40 2T Diesel Engine Oil</b>
Summary	<b>Product description</b> SINOPEC TULUX CF-2 40 2T Diesel Engine Oil is formulated with high-quality base oil and a multifunctional additive system. Formulated especially for severe duty, two-stroke cycle diesel engine applications.

Available sizes



PAIL – 18L



DRUM – 200L

## Applications

- Severe duty two-stroke cycle diesel engine applications that require a monograde API CF-2 or CD-II oil

## Features and benefits

- Excellent deposit control characteristics reduce the buildup of combustion chamber and valve-seat deposits, reducing wear and ensuring effective engine operation.
- Medium-ash formulation reduces the incidence of valve guttering.
- Good thermal and oxidation stability together with good detergency properties, ensures the oil not to break down or thicken at high temperatures, keeps the engine clean and extends component life.
- Excellent lubricity and anti-wear properties protect against engine wear and extend engine life.

## Typical data

<b>SINOPEC TULUX CF-2 40 2T Diesel Engine Oil</b>	
SAE grade	40
Kinematic viscosity, ASTM D 445	
cSt @ 40°C	147.6
cSt @ 100°C	14.85
Viscosity index, ASTM D 2270	100
Sulfated ash, wt%, ASTM D 874	1.64
Total base number, mg KOH/g, ASTM D 2896	13.3
Pour point, °C, ASTM D 97	-13
Flash point (COC), °C, ASTM D 92	256
Density @ 20°C, kg/l, ASTM D 4052	0.894

These data are given as an indication of typical values, not exact specifications.

## Industry and OEM specifications

<b>SINOPEC TULUX CF-2 40 2T Diesel Engine Oil meets the performance requirements of the following industry specifications:</b>	
API Service Classification	Diesel: CF-2

## Accuracy of information

Data provided in this PDS is typical and subject to change as a result of continuing product research and development. The information given was correct at the time of printing. The typical values given are subject to variations in the testing procedures and the manufacturing process may also result in slight variations. Sinopec guarantees that its lubricants meet any industry and OEM specifications referred to on this data sheet.

Sinopec cannot be held responsible for any deterioration in the product due to incorrect storage or handling. Information on best practice is available from your local distributor.

## Product and environmental safety

This product should not cause any health problems when used in the applications suggested and when the guidance provided in the Safety Data Sheet (SDS) is followed. Please consult the SDS for more detailed advice on handling; SDSs are available from your local distributor. Do not use the product in applications other than those suggested.

As with all products, please take care to avoid environmental contamination when disposing of this product. Used oil should be sent for reclamation/recycling or, if not possible, must be disposed of according to relevant government/authority regulations.

The SINOPEC trademark is registered and protected.

Issued: March 2023

© Sinopec 2023

SINOPEC TULUX CF-2 40 2T Diesel Engine Oil