

Safety Data Sheet

According to SS586:2014

Tulux CF/SF 30 Diesel Engine Oil

Version 1.0

Issue date: 03/02/2015

Revision date: 03/02/2015 SDS Record Number:

CSSS-TCO-010-116194

Section 1 Identification of the substance/mixture and of the company/undertaking

Product identifier:

Identification on the label/Trade name: Tulux CF/SF 30 Diesel Engine Oil

Additional identification:

Identification of the product:

Index Number:

REACH registration No.:

Not available

Not available

Relevant identified uses of the substance and uses advised against:

Identified uses:

Can be used in gasoline/diesel engine for lubricating, cooling and airproofing etc.

Uses advised against:

Not available.

Details of the supplier of the safety data sheet:

Supplier(Manufacturer): SINOPEC LUBRICANT CO., LTD.

Address: No. 6 Anning Zhuang West Road, Haidian District, Beijing, P.R.China

Contact person(E-mail): csc.lube@sinopec.com

Telephone: 86-400-810-9886 Fax: 86-10-82410856

Emergency telephone Number:

86-400-810-9886 Only available during office hours (8:30a.m.-17:30p.m. Beijing Time Zone)

Available outside office hours? YES NO X

Section 2 Hazards Identification

Classification of the substance/mixture:

GHS Classification Not classified

label elements:

Hazard Pictograms: No hazard pictogram is used.

Signal Word(S): No signal word is used.

Hazard Statement:Not applicable.Precautionary statement:Not applicable.

Other hazards:

Not available.

Section 3 Composition/information on ingredients

Substance/Mixture: Mixture

Product name: Tulux CF/SF 30 Diesel Engine Oil

Version #: 1.0 Issue date: 03-02-2015. Revision date: 03-02-2015. 1 / 7

Ingredient(s):

Chemical Name	Registration No.	CAS No.	EC No.	Concentration
Base oil	N/A	64742-44-5	265-146-1	80-90%
Additive	N/A	Mixture	N/A	<20%

Section 4 First aid measures

Description of first aid measures:

In all cases of doubt, or when symptoms persist, seek medical attention.

In case of inhalation:

No specific first aid measures are required. If exposed to excessive levels of material in the air, move the exposed person to fresh air. Get medical attention if coughing or respiratory discomfort occurs.

In case of skin contact:

No specific first aid measures are required. As a precaution, remove clothing and shoes if contaminated. To remove the material from skin, use soap and water. Discard contaminated clothing and shoes or thoroughly clean before reuse.

In case of eyes contact:

No specific first aid measures are required. As a precaution, remove contact lenses, if worn, and flush eyes with water.

In case of ingestion:

No specific first aid measures are required. Do not induce vomiting. As a precaution, get medical advice.

Most important symptoms and effects, both acute and delayed:

The product is not classified as harmful to human health effect.

Indication of any immediate medical attention and special treatment needed:

If skin irritation or rash occurs, get medical advice/attention.

Section 5 Fire-Fighting measures

Extinguishing media:

Suitable extinguishing media: Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish flames.

Unsuitable extinguishing media: Water.

Special hazards arising from the

substance or mixture

This material will burn although it is not easily ignited. Highly dependent on combustion conditions. A complex mixture of airborne solids, liquids, and gases including carbon monoxide, carbon dioxide, and unidentified organic compounds

will be evolved when this material undergoes combustion.

Special fire fighting methods and

special protective actions for

fire-fighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel: Provide adequate ventilation. Avoid inhalation of vapour. Avoid skin and eye

contact. Refer to section 8 of SDS for personal protection details.

For emergency responders: Wear an appropriate NIOSH/MSHA approved respirator if dust is generated.

Environmental Precautions: Do not allow material to be released to the environment without proper

governmental permits.

Product name: Tulux CF/SF 30 Diesel Engine Oil
Version #: 1.0 Issue date: 03-02-2015. Revision date: 03-02-2015. 2 / 7

Methods for Containment and Cleaning up:

Stop the source of the release if you can do it without risk. Clean up spill as soon as possible, observing precautions in Exposure Controls/Personal Protection. Use appropriate techniques such as applying non-combustible absorbent materials or pumping. Where feasible and appropriate, remove contaminated soil. Place contaminated materials in disposable containers and dispose of in a manner

consistent with applicable regulations.

Reference to other sections: See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

Additional information: Not applicable.

Section 7 Handling and storage

Precautions for safe handling:

Protective measures: Electrostatic charge may accumulate and create a hazardous condition when

handling this material. To minimize this hazard, bonding and grounding may be necessary but may not, by themselves, be sufficient. Review all operations which have the potential of generating and accumulating an electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum

truck operations) and use appropriate mitigating procedures.

Advice on general occupational hygiene: Do not eat, drink and smoke in work areas. Wash hands after use. Remove

contaminated clothing and protective equipment before entering eating areas.

Conditions for safe storage, including

any incompatibilities:

Store in original containers. Keep containers securely sealed. No smoking, naked lights or ignition sources. Store in a cool, dry, well-ventilated area. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat,

flame, sparks, static electricity, or other sources of ignition.

Specific end use(s): Not applicable.

Section 8 Exposure Controls/Personal Protection

Control parameters:

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA:

Not Available

EMERGENCY LIMITS:

Not Available

Ingredient	Original IDLH	Revised IDLH
Base oil (CAS#64742-44-5)	Not Available	Not Available

Exposure controls:

Appropriate engineering controls: Use in a well-ventilated area. Individual protection measures, such as personal protective equipment:

Eye/face protection: No special eye protection is normally required. Where splashing is possible, wear

safety glasses with side shields as a good safety practice.

Hand protection: Suggested materials for protective gloves include: Neoprene, Nitrile Rubber.

Body protection: No special protective clothing is normally required. Where splashing is possible,

Product name: Tulux CF/SF 30 Diesel Engine Oil
Version #: 1.0 Issue date: 03-02-2015. Revision date: 03-02-2015. 3 / 7

select protective clothing depending on operations conducted, physical

requirements and other substances in the workplace.

Respiratory protection: No respiratory protection is normally required. No respiratory protection is ordinarily

required under normal conditions of use. In accordance with good industrial hygiene

practices, precautions should be taken to avoid breathing of material...If user

operations generate an oil mist, determine if airborne concentrations are below the occupational exposure limit for mineral oil mist. If not, wear an approved respirator

that provides adequate protection from the measured concentrations of this

material. For air-purifying respirators use a particulate cartridge. Use a positive pressure air-supplying respirator in circumstances where air-purifying respirators

may not provide adequate protection.

Thermal hazards: Wear suitable protective clothing to prevent heat.

Environmental exposure controls: Avoid discharge into the environment.

According to local regulations, Federal and official regulations.

Section 9 Physical and chemical properties

Information on basic physical and chemical properties:

Appearance: Liquid

Colour: Transparent, brown Odour: Odorless or slight odor

Odour threshold: Not available pH: Not available Not available Melting point/range (°C): Boiling point/range (°C): Not available

250 °C (Open Cup)(typical) Flash point (°C):

Evaporation rate: Not available Flammability limit - lower (%): Not available Flammability (solid, gas): Not available Ignition temperature (°C): Not available Upper/lower flammability/explosive limits: Not available Vapour pressure (20°C): Not available Vapour density: Not available

0.80kg/L~0.90kg/L (20°C) Density:

Bulk density (kg/m³): Not available

Water solubility (g/l): Insoluble in water. n-Octanol/Water (log Po/w): > 6 (estimated value)

Auto-ignition temperature: >260°C

Decomposition temperature: Not available

Viscosity, dynamic (mPa.s): 10.2 mm2/s - 12.2 mm2/s (100°C)

Explosive properties: Not available Not available Oxidising properties: Molecular Formula: Not available Molecular Weight: Not available

Product name: Tulux CF/SF 30 Diesel Engine Oil Revision date: 03-02-2015. Version #: 1.0 Issue date: 03-02-2015.

Other information:

Fat solubility(solvent- oil to be specified)

Soluble in hydrocarbon solvents

Surface tension: Not available Dissociation constant in water(pKa): Not available **Oxidation-reduction Potential:** Not available Specific gravity: Not available

Section 10 Stability and reactivity

Reactivity: The substance is stable under normal storage and handling conditions.

Chemical stability: Stable at room temperature in closed containers under normal storage and handling

conditions.

Possibility of hazardous reactions: May react with strong oxidizing agents.

Conditions to avoid: Incompatible materials. Avoid extreme temperatures, sun exposure, the fire source.

Incompatible materials: Strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

Hazardous decomposition products: A complex mixture of airborne solids, liquids, and gases including carbon monoxide,

carbon dioxide, and unidentified organic compounds will be evolved when this

material undergoes combustion.

Section 11 Toxicological information

Toxicokinetics, metabolism and distribution:

Non-human toxikological data: Not available

Information on toxicological effects:

Acute toxicity:

LD50(Oral, Rat): >5g/kg LD50(Dermal, Rabbit): >5g/kg LC50(Inhalation, Rat): >10g/m3

Acute toxicity:

Base oil (CAS: 64742-44-5)

LD50(Oral, Rat): > 5000 mg/kg bw LD50(Dermal, Rabbit): > 2000 mg/kg bw LC50(Inhalation, Rat): 2.18 mg/L air Skin corrosion/Irritation: Not classified Serious eye damage/irritation: Not classified Respiratory or skin sensitization: Not classified Not classified Germ cell mutagenicity: Not classified Carcinogenicity: Not classified Reproductive toxicity: Not classified STOT- single exposure: STOT-repeated exposure: Not classified

Section 12 Ecological information

Toxicity:

Product name: Tulux CF/SF 30 Diesel Engine Oil SDS SG Revision date: 03-02-2015. Version #: 1.0 Issue date: 03-02-2015. 5/7

Acute t	oxicity	Time	Species	Method	Evaluation	Remarks
LC50	N/A	96h	Fish	OECD 203	N/A	N/A
EC50	N/A	48h	Daphnia	OECD 202	N/A	N/A
EC50	N/A	72h	Algae	OECD 201	N/A	N/A

Persistence and degradability: This material is not expected to be readily biodegradable.

Bioaccumulative potential: This material contains components with potential to bioaccumulation.

Mobility in soil: If into the soil, this material will be adsorbed and not flow.

Results of PBT&vPvB assessment: Not available. Other adverse effects: Not available.

Section 13 Disposal considerations

Waste treatment methods: The material should be disposed of by incineration in a chemical incinerator in

compliance with national and regional requirements.

Product / Packaging disposal: If empty container retains product residues, all label precautions must be observed.

Return for reuse or dispose according to national or local regulations.

Section 14 Transport information			
	Land transport(ADR/RID)	Sea transport (IMDG)	Air transport (ICAO/IATA)
UN-Number	Not regulated	Not regulated	Not regulated
UN Proper shipping name	Not regulated	Not regulated	Not regulated
Transport hazard Class	Not regulated	Not regulated	Not regulated
Packaging group	Not regulated	Not regulated	Not regulated
Environmental hazards	No	No	No
Special precautions for user	See section 2.2	See section 2.2	See section 2.2
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not regulated	Not regulated	Not regulated

Section 15 Regulation information

Safety, health and environmental regulations/legislation specific for the substance or mixture:

Base oil (64742-44-5) is found on the following	Not applicable
regulatory lists	

Section 16 Other information

Further information:

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

Notice to reader:

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgment of suitability of this information to ensure proper use and protect the health and safety of employees. This information is

SDS SG Revision date: 03-02-2015. Version #: 1.0 Issue date: 03-02-2015. 6/7

furnished without warranty, and any use of the product not in conformance with this Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

Author: Hangzhou CIRS Co., Limited Website:www.cirs-group.com Tel:0571-87206555 Email:info@cirs-group.com

Product name: Tulux CF/SF 30 Diesel Engine Oil SDS SG Version #: 1.0 Issue date: 03-02-2015. Revision date: 03-02-2015.