

Safety Data Sheet

According to SS586:2014

TO-4 60 Heavy Duty Transmission Fluid

Version 1.0

Issue date: 03/02/2015

Revision date: 03/02/2015 SDS Record Number: CSSS-TCO-010-116190

Section 1 Identification of the substance/mixture and of the company/undertaking

Pι	00	uk	ct	ide	en	tifi	er	:
----	----	----	----	-----	----	------	----	---

Identification on the label/Trade name: TO-4 60 Heavy Duty Transmission Fluid

Additional identification: Not available Identification of the product: See section 3 Not available Index Number: Not available REACH registration No.:

Relevant identified uses of the substance and uses advised against:

Identified uses:

Suitable for heavy-duty transmissions, gearboxes, final drives and hydraulic systems used in off-highway applications, where a Caterpillar TO-4 product is recommended.

Uses advised against:

Not available.

Details of the supplier of the safety data sheet:

SINOPEC LUBRICANT CO., LTD. Supplier(Manufacturer):

Contact person(E-mail): csc.lube@sinopec.com

86-400-810-9886 Telephone: 86-10-82410856 Fax:

Emergency telephone Number:

86-400-810-9886 Only available during office hours (8:30a.m.-17:30p.m. Beijing Time Zone)

Available outside office hours? YES NO Χ

Section 2 Hazards Identification

Classification of the substance/mixture:

GHS Classification Not classified

label elements:

Hazard Pictograms: No hazard pictogram is used.

Signal Word(S): No signal word is used.

Hazard Statement: Not applicable. **Precautionary statement:** Not applicable.

Other hazards:

Not available.

Section 3 Composition/information on ingredients

Substance/Mixture: Mixture

Product name: TO-4 60 Heavy Duty Transmission Fluid SDS SG Version #: 1.0 Issue date: 03-02-2015. 1/7

Ingredient(s):

Chemical Name	Registration No.	CAS No.	EC No.	Concentration
Highly refined mineral oil	N/A	64742-65-0	265-169-7	90-99%
Additive package	N/A	-	-	<10%

Section 4 First aid measures

Description of first aid measures:

In all cases of doubt, or when symptoms persist, seek medical attention.

In case of inhalation:

No specific first aid measures are required. If exposed to excessive levels of material in the air, move the exposed person to fresh air. Get medical attention if coughing or respiratory discomfort occurs.

In case of skin contact:

No specific first aid measures are required. As a precaution, remove clothing and shoes if contaminated. To remove the material from skin, use soap and water. Discard contaminated clothing and shoes or thoroughly clean before reuse.

In case of eyes contact:

No specific first aid measures are required. As a precaution, remove contact lenses, if worn, and flush eyes with water.

In case of ingestion:

No specific first aid measures are required. Do not induce vomiting. As a precaution, get medical advice.

Most important symptoms and effects, both acute and delayed:

The product is not classified as harmful to human health effect.

Indication of any immediate medical attention and special treatment needed:

If skin irritation or rash occurs, get medical advice/attention.

Section 5 Fire-Fighting measures

Extinguishing media:

Suitable extinguishing media: Use water fog, foam, dry chemical or carbon dioxide to extinguish flames.

Unsuitable extinguishing media: Water.

Special hazards arising from the

substance or mixture

In case of heat, fire and strong oxidants can lead to burning. Fumes, smoke, carbon monoxide, sulfur oxides, aldehydes, nitrogen oxides, phosphate, certain metal

oxides and other decomposition products, in the case of incomplete combustion.

Special fire fighting methods and special protective actions for

fire-fighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

mode.

Section 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel: Provide adequate ventilation. Avoid skin and eye contact. Refer to section 8 of SDS

for personal protection details.

For emergency responders: Wear an appropriate NIOSH/MSHA approved respirator if dust is generated.

Environmental Precautions: Do not allow material to be released to the environment without proper

governmental permits.

Methods for Containment and Cleaning up: Stop the source of the release if you can do it without risk. Contain release to

Product name: TO-4 60 Heavy Duty Transmission Fluid

Version #: 1.0 Issue date: 03-02-2015. Revision date: 03-02-2015. 2 / 7

prevent further contamination of soil, surface water or groundwater. Clean up spill as soon as possible, observing precautions in Exposure Controls/Personal Protection. Use appropriate techniques such as applying non-combustible absorbent materials or pumping. Where feasible and appropriate, remove contaminated soil. Place contaminated materials in disposable containers and dispose of in a manner consistent with applicable regulations.

Reference to other sections: See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

Additional information: Not applicable.

Section 7 Handling and storage

Precautions for safe handling:

Protective measures: Containers, even those that have been emptied, may contain explosive vapours. Do

NOT cut, drill, grind, weld or perform similar operations on or near containers. Electrostatic discharge may be generated during pumping - this may result in fire.

Ensure electrical continuity by bonding and grounding (earthing) all equipment.

Advice on general occupational hygiene: Do not eat, drink and smoke in work areas. Wash hands after use. Remove

contaminated clothing and protective equipment before entering eating areas.

Conditions for safe storage, including

any incompatibilities:

Do not store in open or unlabeled containers. Store in a cool, dry place with adequate ventilation. Keep away from open flames and high temperatures.

Specific end use(s): Not applicable.

Section 8 Exposure Controls/Personal Protection

Control parameters:

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA:

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US ACGIH Threshold	Highly refined	Mineral oil, excluding	5 mg/m ³	Not Available	Not Available	TLV® Basis:
Limit Values (TLV)	mineral oil	metal working fluids -				URT irr
		Pure, highly and				
		severely refined /				
		Mineral oil, excluding				
		metal working fluids -				
		Poorly and mildly				
		refined				

EMERGENCY LIMITS:

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
Highly refined mineral oil	Pump oil	15 mg/m ³	170 mg/m ³	990 mg/m ³

Ingredient	Original IDLH	Revised IDLH
Highly refined mineral oil	Not Available	Not Available

Exposure controls:

Appropriate engineering controls: Provide adequate ventilation to control airborne concentrations below the exposure

guidelines/limits.

Individual protection measures, such as personal protective equipment:

Eye/face protection: No special eye protection is normally required. Where splashing is possible, wear

Product name: TO-4 60 Heavy Duty Transmission Fluid

Version #: 1.0 Issue date: 03-02-2015. Revision date: 03-02-2015. 3 / 7

safety glasses with side shields as a good safety practice.

Hand protection: Use protective gloves which is chemically resistant to this material.

Body protection: No special protective clothing is normally required. Where splashing is possible,

select protective clothing depending on operations conducted, physical requirements and other substances in the workplace. Suggested materials for

protective gloves include: Neoprene, Nitrile rubber.

Respiratory protection: No respiratory protection is normally required. No respiratory protection is ordinarily

required under normal conditions of use. In accordance with good industrial hygiene

practices, precautions should be taken to avoid breathing of material. If user

operations generate an oil mist, determine if airborne concentrations are below the occupational exposure limit for mineral oil mist. If not, wear an approved respirator

that provides adequate protection from the measured concentrations of this material. For air-purifying respirators use a particulate cartridge. Use a positive pressure air-supplying respirator in circumstances where air-purifying respirators

may not provide adequate protection.

Thermal hazards: Wear suitable protective clothing to prevent heat.

Environmental exposure controls: Avoid discharge into the environment.

According to local regulations, Federal and official regulations.

Section 9 Physical and chemical properties

Information on basic physical and chemical properties:

Appearance: Yellow to brown transparent oily liquid

Colour: Yellow to brown

Odorless or slight odor

Odour threshold:

pH:

Not available

Not available

Melting point/range (°C):

Not available

> 280 °C (typ)

Flash point (°C): 250 °C (open cup) (typ)

Evaporation rate:

Flammability limit - lower (%):

Flammability (solid, gas):

Ignition temperature (°C):

Upper/lower flammability/explosive limits:

Vapour pressure (40°C):

Vapour density:

Not available

<0.5Pa(20°C)

>1(air=1)

Density: 0.84 kg/l - 0.93 kg/l(20°C)

Bulk density (kg/m³): Not available
Water solubility (g/l): Insoluble

n-Octanol/Water (log Po/w): > 6 (estimated value)

Auto-ignition temperature: >320°C

Decomposition temperature: Not available

Viscosity: 10.6 mm/s² -12.5 mm/s² (100°C)

Product name: TO-4 60 Heavy Duty Transmission Fluid

Version #: 1.0 Issue date: 03-02-2015. Revision date: 03-02-2015. 4 / 7

Explosive properties: Non explosive Oxidising properties: Not oxidizing Molecular Formula: Not available **Molecular Weight:** Not available

Other information:

Fat solubility(solvent- oil to be specified)

etc:

Not available

Surface tension: Not available Dissociation constant in water(pKa): Not available **Oxidation-reduction Potential:** Not available Specific gravity: Not available

Section 10 Stability and reactivity

Reactivity: The substance is stable under normal storage and handling conditions.

Stable at room temperature in closed containers under normal storage and handling Chemical stability:

conditions.

Possibility of hazardous reactions: Contact with strong oxidants can lead to burning.

Conditions to avoid: Extreme heat and high energy sources of ignition and strong oxidizers.

Incompatible materials: Strong oxidizing agents.

Hazardous decomposition products: Fumes, smoke, carbon monoxide, sulfur oxides, aldehydes, nitrogen oxides,

phosphate, certain metal oxides and other decomposition products, in the case of

incomplete combustion.

Section 11 Toxicological information

Toxicokinetics, metabolism and distribution:

Non-human toxikological data: Not available

Information on toxicological effects:

Acute toxicity:

LD50(Oral, Rat): > 5000 mg/kg bw LD50(Dermal, Rabbit): > 5000 mg/kg bw > 10000 mg/m³ bw LC50(Inhalation, Rat): Skin corrosion/Irritation: Not classified

Serious eye damage/irritation: Not classified Not classified Respiratory or skin sensitization: Not classified Germ cell mutagenicity: Carcinogenicity: Not classified Reproductive toxicity: Not classified STOT- single exposure: Not classified STOT-repeated exposure: Not classified

Section 12 Ecological information

Toxicity: Highly refined mineral oil (CAS: 64742-65-0):

Acute toxicity Time Openies Wethou Evaluation Nemarks	Acute toxicity	Time	Species	Method	Evaluation	Remarks
---	----------------	------	---------	--------	------------	---------

LL50	> 100 mg/L	96h	Fish	OECD 203	N/A	N/A
LL50	> 10000 mg/L	48h	Daphnia	OECD 202	N/A	N/A
EC50	N/A	72h	Algae	OECD 201	N/A	N/A

Persistence and degradability: This product is expected to be inherently biodegradable.

Bioaccumulation is unlikely due to the very low water solubility of this product;

Bioaccumulative potential: therefore bioavailability to aquatic organisms is minimal.

When released into the environment, adsorption to sediment and soil will Be the

predominant behavior.

Results of PBT&vPvB assessment: Not available.

Other adverse effects: Not available.

Section 13 Disposal considerations

Mobility in soil:

Waste treatment methods: The material should be disposed of by incineration in a chemical incinerator in

compliance with national and regional requirements.

Product / Packaging disposal: If empty container retains product residues, all label precautions must be observed.

Return for reuse or dispose according to national or local regulations.

Section 14 Transport information					
	Land transport(ADR/RID)	Sea transport (IMDG)	Air transport (ICAO/IATA)		
UN-Number	Not regulated	Not regulated	Not regulated		
UN Proper shipping name	Not regulated	Not regulated	Not regulated		
Transport hazard Class	Not regulated	Not regulated	Not regulated		
Packaging group	Not regulated	Not regulated	Not regulated		
Environmental hazards	No	No	No		
Special precautions for user	See section 2.2	See section 2.2	See section 2.2		
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not regulated	Not regulated	Not regulated		

Section 15 Regulation information

Safety, health and environmental regulations/legislation specific for the substance or mixture:

Highly refined mineral oil (64742-65-0) is found on the	"Not Applicable"
following regulatory lists	

Section 16 Other information

Further information:

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

Notice to reader:

Employers should use this information only as a supplement to other information gathered by them, and should make independent

Product name: TO-4 60 Heavy Duty Transmission Fluid SDS SG

judgment of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

Product name: TO-4 60 Heavy Duty Transmission Fluid

Version #: 1.0 Issue date: 03-02-2015. Revision date: 03-02-2015.

SDS SG
7 / 7